

Ceiling mounts

for projectors

The projector is not only important element in a professional installation.

Features such as fast installation, easy adjustment and stability of any accessories are just as important.



Audipack®

It's great to have solutions...

Ultimate flexibility

with Audipack ceiling mounts



Quatro-Fix®, the allrounder

The Quatro-Fix projector mounts offers maximum flexibility to set up any projector up to 20kg within the most complex of installs.

The Quatro-Fix® ceiling mounts and the brand compatible mounts are equipped with a special newly designed ball joint that allows you to position the projector with minimal effort. The ball joint is designed to rotate from its own point of gravity. This results in a flexible and almost friction free adjustment capability.

UTS, for projector mounts and more.

Audipack also offers brand compatible projector mounts combined with the UTS (**U**niversal **T**ube **S**et) for any brand or type of projector, from stock. Brand compatible mounts are always a perfect fit and comply with manufacturers' installation guides and standards. For this type of ceiling mount an additional projector or camera mount is needed to complete the set.

UTS + brand related mount = the perfect solution



- ▲ **Rigid and safe construction**
- ▲ **Any configuration possible**
- ▲ **Very flexible**
- ▲ **Integrated cable ducts**

Quick release, the perfect AV rental solution ...

Look no further for a ceiling mount that allows the fast and easy exchange of projectors. The quick release ball joint allows swift and safe installation. Especially designed for professional rental and stage use. (see page 131)



Angle adjustment



Perfect adjustment with telescopic feature




Cable passage



Cable passage

QUATRO-FIX

Max. load



Mounting range in mm
440 in diameter



Angle adjustment in degrees 15° + 15°

Ref.	QFIX-0100			
Length in mm	100			
Tube diameter in mm	54			
Ref.	QFIX-0300			
Length in mm	300			
Tube diameter in mm	54			
Ref.	QFIX-0500T			
Length in mm	355-500			
Tube diameter in mm	54-60			
Ref.	QFIX-0700T			
Length in mm	450-700			
Tube diameter in mm	54-60			
Ref.	QFIX-1000T			
Length in mm	604-1000			
Tube diameter in mm	54-60			

QUATRO-FIX XL



Mounting range in mm
W336 x D 382



Angle adjustment in degrees 15° + 15°

Ref.	QFIX3-0100			
Length in mm	100			
Tube diameter in mm	54			
Ref.	QFIX3-0300			
Length in mm	300			
Tube diameter in mm	54			
Ref.	QFIX3-0500T			
Length in mm	355-500			
Tube diameter in mm	54-60			
Ref.	QFIX3-0700T			
Length in mm	450-700			
Tube diameter in mm	54-60			
Ref.	QFIX3-1000T			
Length in mm	604-1000			
Tube diameter in mm	54-60			

UNIVERSAL TUBE SET



Angle adjustment in degrees 15° + 15°

Ref.	UTS-0100			
Length in mm	100			
Tube diameter in mm	54			
Ref.	UTS-0300			
Length in mm	300			
Tube diameter in mm	54			
Ref.	UTS-0500T			
Length in mm	355-500			
Tube diameter in mm	54-60			
Ref.	UTS-0700T			
Length in mm	450-700			
Tube diameter in mm	54-60			
Ref.	UTS-1000T			
Length in mm	604-1000			
Tube diameter in mm	54-60			

CEILING MOUNTS

HEAVY DUTY PROJECTOR CEILING MOUNT

Ref.	390065
Length in mm	164
Tube diameter in mm	45
Angle adjustment in degrees	20° + 20°



360°

Ref.	390061
Length in mm	697-937
Tube diameter in mm	45-50
Angle adjustment in degrees	20° + 20°

**QUICK RELEASE PROJECTOR CEILING MOUNT**

Ref.	392165
Length in mm	142
Tube diameter in mm	45
Angle adjustment in degrees	30° + 30°



360°

Ref.	392161
Length in mm	675-915
Tube diameter in mm	45-50
Angle adjustment in degrees	30° + 30°

**QUICK RELEASE PLUS PROJECTOR CEILING MOUNT WITH 3D ADJUSTMENT**

Ref.	392365
Length in mm	193
Tube diameter in mm	45
Angle adjustment in degrees	30° + 30°
Fine tune adjustment in degrees	-3°, +3°

3D
ADJUSTMENT

Ref.	392361
Length in mm	726-966
Tube diameter in mm	45-50
Angle adjustment in degrees	30° + 30°
Fine tune adjustment in degrees	-3°, +3°

**QUICK RELEASE PLUS + CEILING MOUNT WITH 3D ADJUSTMENT & HORIZONTAL SHIFT**

Ref.	392665
Length in mm	193
Tube diameter in mm	45
Angle adjustment in degrees	30° + 30°
Fine tune adjustment in degrees	-3°, +3°
Horizontal shift in mm	60

3D
ADJUSTMENT

Ref.	392661
Length in mm	675-915
Tube diameter in mm	45-50
Angle adjustment in degrees	30° + 30°
Fine tune adjustment in degrees	-3°, +3°
Horizontal shift in mm	60



ACCESSORIES

PROJECTOR MOUNTS (SEE PAGE 123 FOR THE FULL PROGRAM)

Mount any brand and type of projector on any Audipack system with the Audipack projector mounts.



Quatro-Fix® **Brand related mounts**

EXTENSION TUBES (ONLY SUITABLE FOR THE QUATRO-FIX® AND THE UTS)



Diameter 54 mm.

Ref.	ET-1000	ET-1500	ET-2000	ET-2500
Length in mm	1000	1500	2000	2500
Length gain in mm	940	1440	1940	2440

EXTENSION TUBES (ONLY SUITABLE FOR HEAVY DUTY AND QUICK RELEASE TUBE SETS)



Diameter 45 mm.

Ref.	390022	390066	390367	390210	390321	390211
Length in mm	750	1000	1250	1500	1750	2000
Length gain in mm	350	600	850	1100	1350	1600

SHOCK ABSORBER, FOR CEILING MOUNTS



Ref. 392193
Suitable for 390065, 390061, 392165, 392161, 392365, 392361, 392665, 392661

EQUIPMENT CABINET (UNIVERSAL)



Ref.
Max. equipment dimensions in mm

EC-5
W 350 x D 350 x H 100

CAMERA SUPPORT



Ref. **CS-1** (Only suitable for 54 mm diameter tubes)

CEILING MOUNTS

QUICK RELEASE COUPLER

		 
<p>Ref. Suitable for Max. load</p>	<p>BJ-1QR Q-fix, UTC, UTS 10 Kg</p>	

3D ADJUSTMENT FOR BALL JOINTS

			 
<p>Ref. Feature Suitable for</p>	<p>BJ-3D1 3D fine tuning Q-fix, UTC, UTS</p>	<p>BJ-3D1S 3D fine tuning & side shift Q-fix, UTC, UTS</p>	

TRUSS MOUNTS

			
<p>Ref. Suitable for</p>	<p>TM-54 54 mm (Q-fix & UTS only)</p>	<p>TM-60 (Telescopic tube sets only) 60 mm (Q-fix & UTS only)</p>	<p>260140 All "39....." products</p>

SEVERAL OPTIONS

			
<p>Ref. Type Suitable for</p>	<p>390199 Manual rotation All "39....." tube sets</p>	<p>392150 Construction clamp All</p>	<p>399941</p>

CEILING MOUNT PLATES WITH TILT ADJUSTMENT

	<p>Adjustment: -5° to +90°</p> 	<p>Standard on:</p> <p>QFIX-0500T UTS-0500T QFIX-0700T UTS-0700T QFIX-1000T UTS-1000T QFIX3-0500T QFIX3-0700T QFIX3-1000T</p> 
<p>Ref. Suitable for</p>	<p>CMP-4 60 mm tubes</p>	<p>CMP-5 54 mm tubes</p>